


UNITEC TUV SPAN 300

Designed to meet Work
at Height Regulations

Suitable for Electrical
Applications

CERTIFIED:
DIN EN 1004:2005-05
ANSI A10.8
CAN/CSA-S269.2-M87

SERIES:
29"/0,73m Narrow Width
54"/1,37m Double Width
6'-8'-10'/2,00-2,50-3,00m Length




COMPONENTS




Base Plate
cod. BP00




Castor sizes:
cod. 93633 Ø 127mm
cod. 62152 Ø 203mm



Horizontal brace lengths:
2,00m cod. UHB06
2,50m cod. UHB08
3,05m cod. UHB10




Diagonal brace lengths:
2,00m cod. UDB06
2,50m cod. UDB08
3,05m cod. UDB10




Handrail frame lengths :
2,00m cod. U24342 06
2,50m cod. U23996 08
3,05m cod. U14997 10

Narrow Base Frames



cod. UQB2906E cod. USB2900E
cod. UQB2908E

Narrow Extension Frames




cod. UEX2964E cod. UEX2956E cod. UEX2946E cod. UEX2939E

Narrow Guardrail Frames




cod. UGR2937


Double Base Frames




cod. UQB5406E
cod. UQB5408E




cod. USB5400E




cod. UEX5464E



cod. UEX5456E




cod. UEX5446E




cod. UEX5439E

Double Extension Frames


Double Guardrail Frame




cod. UEX5437




cod. UST56




cod. UST69




Large Outrigger
cod. PSX66 GRP




Medium Outrigger
cod. PSR42 GRP




Standard platform lengths:
2,00m – cod. USP06-61
2,50m – cod. USP08-61
2,00m – cod. ASP06-61
2,50m – cod. ASP08-61
3,05m – cod. ASP10-61



Hatch platform lengths:
2,00m – cod. UHP06
2,50m – cod. UHP08
2,00m – cod. AHP06
2,50m – cod. AHP08
3,05m – cod. AHP10



Narrow Toeboard lengths:
2,00m cod. WTB2906
2,50m cod. WTB2908
2,00m cod. ATB2906
2,50m cod. ATB2908
3,05m cod. ATB2910



Double Toeboard lengths:
2,00m cod. WTB5406
2,50m cod. WTB5408
2,00m cod. ATB5406
2,50m cod. ATB5408
3,05m cod. ATB5410